Product data sheet

Slimdrive SL RC2-FR drive

Automatic linear sliding door drive with burglar resistance in accordance with resistance class 2

AREAS OF APPLICATION

- Single and double leaf sliding door systems along escape and rescue routes
- Interior and exterior doors with maximum safety requirements
- Opening widths of 800 to 3000 mm possible
- Suitable profile systems are fine-framed profile systems with ISO and mono glass, in accordance with the resistance class 2 (RC2)

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com

2026-10-10T03:14:35Z

Slimdrive SL RC2-FR drive

PRODUCT FEATURES

- Certified burglar resistance according to resistance class RC2
- The RC2 function is only available in 'night mode' if the door no longer needs to meet escape route requirements.
- Equipped with a rod locking and reinforced profile components
- Very quiet running, low-wear direct current drive with a height of only 7 cm
- Can be networked, and integrated into the building automation via open standard (BACnet)
- Independent error recognition and recording

TECHNICAL DATA

Productname	Slimdrive SL RC2-FR drive
Service temperature	-15 - 50 °C

NETWORKING

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Supply voltage	Output voltage	Output current (max.)
Slimdrive SL RC2-FR drive	Drive system for automatic linear sliding doors using the latest technology	133462	230 V	24 V	1 A