Product data sheet

Link arm TS 4000 / 2000

With mechanical hold-open device

AREAS OF APPLICATION

- To hold open non-fire protection doors
- Right and left single-action doors

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-11-14T03:55:28Z

Link arm TS 4000 / 2000

PRODUCT FEATURES

→ Can be used up to 70 mm reveal depth with transom installation

TECHNICAL DATA

Productname	Link arm TS 4000 / 2000
Hold-open function	Mechanical
Hold-open device can be overridden	Yes
Hold-open range	70 ° - 150 °
Smoke switch integrated	No

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Hold-open point min.	Hold-open point max.
Link arm TS 4000/2000 / F *	With mechanical hold-open device	152365	black RAL 9005	70 °	150 °
Link arm TS 4000/2000 / F	With mechanical hold-open device	102454	silver-coloured	70 °	150 °
Link arm TS 4000/2000 / F	With mechanical hold-open device	102456	white RAL 9016	70 °	150 °
Link arm TS 4000/2000 / F	With mechanical hold-open device	102457	according to RAL	70 °	150 °

INSTALLATION MATERIAL

MOUNTING PLATE LINK ARM *

for TS 4000/TS 2000, with slim frames

Designation	Description	Ident-No.	Colour	Material	EAN
Mounting plate link arm	for TS 4000/TS 2000, with slim frames	082506	according to RAL	Aluminum	4106030825067
Mounting plate link arm	for TS 4000/TS 2000, with slim frames	057109	silver-coloured	Aluminum	4106030571094

Link arm TS 4000 / 2000

MOUNTING PLATE LINK ARM

For TS 4000/TS 2000 for parallel arm installation

Designation	Description	Ident-No.	Colour	Material	EAN
Mounting plate link arm *	for TS 4000/TS 2000, for parallel arm installation	053319	dark bronze	Aluminum	4106030533191
Mounting plate link arm *	for TS 4000/TS 2000, for parallel arm installation	027460	according to RAL	Aluminum	4106030274605
Mounting plate link arm	for TS 4000/TS 2000, for parallel arm installation	053318	silver-coloured	Aluminum	4106030533184

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.