

Product data sheet

ISM guide rail BG TS

5000



With closing sequence control and levers

AREAS OF APPLICATION

- Double leaf doors with closing sequence control
- Installation on the opposite hinge side
- Right and left single-action doors
- Symmetrical and asymmetrical division of door possible
- Up to 2800 mm hinge clearance
- Minimum hinge clearance 1360 mm, minimum width of the passive leaf 380 mm



PRODUCT FEATURES

- Closing sequence control holds the active leaf in the waiting position until the passive leaf is closed
- Horizontally adjustable in the installation position by 4 mm through elongated holes
- With screwed slide block

TECHNICAL DATA

Productname	ISM guide rail BG TS 5000
Minimum hinge clearance	1360 mm
Minimum passive leaf width	380 mm
Standard conformity	EN 1158
Length	2730 mm
Width	55 mm
Height	30 mm
opening restrictor upgradable	Yes
Smoke switch integrated	No
Closing sequence control integrated	Yes
Height correction possible	Yes
Flexible opening restrictor	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions	Type
ISM guide rail BG TS 5000	continuous, with integrated closing sequence control and levers	115597	according to RAL	2730 x 55 x 30 mm	
ISM guide rail BG TS 5000	continuous, with integrated closing sequence control and levers	115596	Stainless steel optic	2730 x 55 x 30 mm	
ISM guide rail BG TS 5000	continuous, with integrated closing sequence control and levers	115594	silver-coloured	2730 x 55 x 30 mm	
ISM guide rail BG TS 5000	continuous, with integrated closing sequence control and levers	115595	white RAL 9016	2730 x 55 x 30 mm	

ACCESSORIES

CB FLEX

Carry bar for safe closing of double leaf fire protection doors



Designation	Description	Ident-No.	Colour
GEZE CB flex	for use on all 2-leaf rebated doors. Concealed length adjustment with variable adjustment up to 210 mm leaf protrusion, hinged mechanism not visible, profile can be shortened if necessary, with attachment material	182652	white RAL 9016
GEZE CB flex	for use on all 2-leaf rebated doors. Concealed length adjustment with variable adjustment up to 210 mm leaf protrusion, hinged mechanism not visible, profile can be shortened if necessary, with attachment material	153602	silver-coloured
GEZE CB flex	for use on all 2-leaf rebated doors. Concealed length adjustment with variable adjustment up to 210 mm leaf protrusion, hinged mechanism not visible, profile can be shortened if necessary, with attachment material	153728	according to RAL

MECHANICAL HOLD-OPEN UNIT

For ISM guide rail



Designation	Description	Ident-No.	Material
Mechanical hold-open unit	for ISM guide rail / ISM guide rail BG, retention force adjustable, can be overridden	118437	Steel

FLEXIBLE OPENING RESTRICTOR

For E and R guide rails, single and double leaf



Designation	Description	Ident-No.	Material
Flexible opening restrictor	for guide rail 1-leaf: TS 5000 E/R/RFS (door leaf installation), Boxer E; 2-leaf: all E/R/ISM variants TS 5000 (incl. VPK) and Boxer	145311	Plastic

ISM guide rail BG TS 5000



KIT ECLINE ISM / ISM BG *

Power storage for use on the active leaf in double leaf ISM and ISM BG guide rails



Designation	Description	Ident-No.	Colour
Kit ECLINE ISM / ISM BG *	Power storage for use on the active leaf in double leaf ISM and ISM BG guide rails	154767	black

INSTALLATION MATERIAL

MOUNTING PLATE *

For ISM / E-ISM / R-ISM guide rail BG & VP versions



Designation	Description	Ident-No.	Colour	Material
Mounting plate guide rail BG	For ISM / E-ISM / R-ISM guide rail BG & VP versions	118705	according to RAL	Aluminum
Mounting plate guide rail BG	For ISM / E-ISM / R-ISM guide rail BG & VP versions	118704	silver-coloured	Aluminum

LINTEL CASING BRACKET

For ISM / E-ISM / R-ISM guide rail BG



Designation	Description	Ident-No.	Colour
Lintel casing bracket	For ISM / E-ISM / R-ISM guide rail BG	118707	according to RAL
Lintel casing bracket	For ISM / E-ISM / R-ISM guide rail BG	118706	silver-coloured

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.