Product data sheet

Hold-open magnet wall installation flush-mounted *

For wall installation flush-mounted

AREAS OF APPLICATION

- Use for hold-open angles up to 180°, ideal for exact holding open
- Use in harsh environments such as industrial buildings
- Places of public assembly and highly frequented sports venues
- Approved for GEZE hold-open systems
- Wall mounting
- Flush-mounted installation

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com

2026-10-03T09:52:49Z

Hold-open magnet wall installation flush-mounted *

PRODUCT FEATURES

- High retention force of 490N
- Concealed line-feed and robust design

TECHNICAL DATA

Productname	Hold-open magnet wall installation flush-mounted *
Dimensions	85 x 85 x 30 mm
IP rating	IP65 Magnet; IP20 connection
Type of installation	Flush-mounted installation
Line-feed	Back side
Area of application	Inside

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Dimensions	Type of installation	IP rating
GEZE door hold-open magnet *	Flush-mounted wall mounting	155567	85 x 85 x 30 mm	Flush-mounted installation	IP65 Magnet; IP20 connection

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.