

Product data sheet

OL 95



Surface-mounted fanlight opener with an opening width of
220 mm

AREAS OF APPLICATION

- Convenient daily ventilation for rooms and staircases
- Inward opening bottom-hung windows
- Can also be used on rectangular windows for inward-opening top-hung windows
- Special forms such as pitched and triangular windows possible
- Installation on wooden, plastic or aluminium windows
- Frame installation

PRODUCT FEATURES

- Achieves the full opening width of 220 mm for all leaf heights
- The opening width can be adjusted
- Little space necessary thanks to flat design of the scissors
- Integrated leaf locking mechanism in the scissors ensures secure locking
- Unhinging inhibitor and lockable hand lever offer additional safety
- The additional locking mechanism increases safety and air-tightness
- Scissor unhooking by pressing the release button facilitates window cleaning from inside and outside
- Completely pre-mounted assembly groups facilitate installation

TECHNICAL DATA

Productname	OL 95
Length	305 mm
Depth	49 mm
Height	16 mm
Opening width (max.)	220 mm
Leaf width (min.)	440 mm
Leaf height (min.)	350 mm
Leaf weight (max.)	60 kg
Fitting stroke	54 mm
Adjustable opening width (stroke reduction)	Dependent
Leaf locking mechanism integrated in the scissors	Yes
Scissor unhooking by release button	Yes
Lockable	Yes
Unhinging inhibitor	Yes

ACCESSORIES**GRIPPING AND CLEANING SCISSORS (FPS)**

For fanlight openers for additional protection of bottom-hung leaves





Designation	Description	Ident-No.	Colour	Dimensions
Gripping and cleaning scissor stay (FPS) Size 1	FPS closing force 1	030249	Galvanised	210 mm
Gripping and cleaning scissor stay (FPS) Size3	FPS closing force 3	030251	Galvanised	410 mm
Gripping and cleaning scissor stay (FPS) Size 2	FPS closing force 2	030250	Galvanised	310 mm