Product data sheet

Removable drip loop *

Guide of the connector cable to the door leaf

AREAS OF APPLICATION

- IQ lock EL/ IQ lock EM/ IQ lock C
- IQ lock EL DL/ IQ lock EM DL/ IQ lock C DL
- IQ lock AUT

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-11-07T03:47:41Z

Removable drip loop *

PRODUCT FEATURES

- Can be detached after door has been fitted by means of integrated plug contacts
- Max. opening angle 180°

TECHNICAL DATA

Productname	Removable drip loop *
Material	Steel
Dimensions	480 x 24 x 17.5 mm

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Dimensions	Type of installation	IP rating
Detachable cable transition (12-pole) *	Detachable cable transition (12-pole) for active leaf without connector cable	152234	480 x 24 x 17.5 mm	in the door frame, in the door leaf	IP20
detachable drip loop (8-pole) *	Detachable drip loop (8-pin) for passive leaf, with 6 m / 3 m connector cable, LiYY 8-core 0.35 mm²	152233	480 x 24 x 17.5 mm	in the door frame	IP67

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.