

# Product data sheet

# Closer body TS 5000

# SoftClose \*



For overhead door closers with guide rail EN 2-6 with individually adjustable closing speed from 0-15° door opening angle

#### AREAS OF APPLICATION

- Fire and smoke protection doors
- Right and left single-action doors
- Single-action doors up to 1400 mm leaf width
- Door leaf installation hinge side and transom installation opposite hinge side

**PRODUCT FEATURES**

- Closing force can be variably adjusted from the front
- Visual closing force display ensures correct setting
- Closing speed can be adjusted from the front via valve
- Latching action / smooth latching function can be adjusted from the front via valve
- Back check can be adjusted from the front via valve
- Door closer, can be used for right and left hand doors
- Minimal installation effort due to low number of individual parts and quick setting

**TECHNICAL DATA**

Productname	Closer body TS 5000 SoftClose *
Closing force in accordance with EN 1154	EN 2 - 6
Leaf width (max.)	1400 mm
Type of installation	Door leaf installation hinge side, Transom installation opposite hinge side
Opening angle (max.)	180 °
Identical design for DIN left and DIN right	Yes
Standard conformity	EN 1154:1996/A1:2002/AC:2006
Suitability for fire protection doors	Yes
Mounting plate with hole pattern in accordance with EN 1154 supplement	Yes
Length	287 mm
Width	47 mm
Height	60 mm
Closing force adjustable	Yes, stepless
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Latching action speed, adjustable	Yes
Back check integrated	Yes, hydraulically adjustable
Position of closing force adjustment	Front
Visual closing force display	Yes
Safety valve against overload	Yes
Thermo-control valves	Yes
Smoke switch integrated	No

# Closer body TS 5000 SoftClose \*



## VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Closing force in accordance with EN 1154	Dimensions
TS 5000 SoftClose door closer *	Closing force EN 2-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	183430	white RAL 9016	EN 2 - 6	287 x 47 x 60 mm
TS 5000 SoftClose door closer *	Closing force EN 2-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	181792	silver-coloured	EN 2 - 6	287 x 47 x 60 mm
TS 5000 SoftClose door closer *	Closing force EN 2-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	181793	according to RAL	EN 2 - 6	287 x 47 x 60 mm
TS 5000 SoftClose door closer *	Closing force EN 2-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	183431	Stainless steel face plate	EN 2 - 6	287 x 47 x 60 mm

## INSTALLATION MATERIAL

### LINTEL CASING BRACKET

for TS 5000/TS 4000



Designation	Description	Ident-No.	Colour	Dimensions
Lintel casing bracket	for TS 5000/TS 4000	049240	silver-coloured	287 x 40 x 67 mm
Lintel casing bracket	for TS 5000/TS 4000	052352	dark bronze	
Lintel casing bracket	for TS 5000/TS 4000	104451	according to RAL	

\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.