Product data sheet

TS 5000 L SoftClose *

Opposite hinge side overhead door closer with guide rail for single-leaf doors up to 1400 mm leaf width with latching action and brake-to-stop function

AREAS OF APPLICATION

- Fire and smoke protection doors
- Right and left single-action doors
- Single-action doors up to 1400 mm leaf width
- Door leaf installation opposite hinge side and transom installation hinge side

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-11-07T03:58:40Z

TS 5000 L SoftClose *

PRODUCT DESCRIPTION

This overhead door closer for single leaf doors represents clear lines. It is authorised for installation on fire and smoke protection doors.

PRODUCT FEATURES

- → Closing force with variable adjustment EN 3-6
- → Can be used for right and left hand doors without conversion
- → Latching action/smooth latching function can be adjusted from the front via valve
- → Closing speed can be individually adjusted
- → Integrated back check, slows down doors that are thrown open forcefully
- → Visual closing force display for easy control of the setting
- → All functions can be adjusted from the front

TECHNICAL DATA

Productname	TS 5000 L SoftClose *
Closing force in accordance with EN 1154	EN 3 - 6
Barrier-free in accordance with DIN 18040 up to leaf width (max.) in mm	1100 mm
Leaf width (max.)	1400 mm
Type of installation	Transom installation hinge side, Door leaf installation opposite hinge side
Opening angle (max.)	120 °
Suitability for fire protection doors	Yes
Closing force adjustable	Yes, stepless
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Latching action speed, adjustable	Yes
Back check integrated	Yes, hydraulically adjustable
Position of closing force adjustment	Front
Visual closing force display	Yes
Hold-open function	Optional
Smoke switch integrated	No

TS 5000 L SoftClose *

PART

GUIDE RAIL BG WALL MOUNTING TS 3/5000 L *

Guide rail for wall installation with lever, opposite hinge side

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Guide rail BG wall mounting TS 3/5000 L *	Guide rail with lever, used with door closer on door leaf installation opposite hinge side	189149	according to RAL	550 x 30.5 x 20.7 mm	4042938891493
Guide rail BG wall mounting TS 3/5000 L *	Guide rail with lever, used with door closer on door leaf installation opposite hinge side	189148	EV1	550 x 30.5 x 20.7 mm	4042938891486

GUIDE RAIL TS 5000 / 3000 VERTICALLY ADJUSTABLE *

With height compensation +/- 2 mm and lever

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Guide rail TS 3/5000 vertically adjustable	Height compensation +/- 2 mm, with lever	115191	silver-coloured	448.5 x 30.5 x 20.5 mm	4042938151917
Guide rail TS 3/5000 vertically adjustable *	Height compensation +/- 2 mm, with lever	115192	according to RAL	448.5 x 30.5 x 20.5 mm	4042938151924

GUIDE RAIL BG TS 5000 / 3000 VERTICALLY ADJUSTABLE *

With height compensation +/- 2 mm, with lever, opposite hinge side

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Guide rail BG TS 3/5000 vertically adjustable *	Height compensation +/- 2 mm, with lever, use with closer on leaf installation on the opposite hinge side	115194	according to RAL	448.5 x 30.5 x 20.5 mm	4042938151948
Guide rail BG TS 3/5000 vertically adjustable *	Height compensation +/- 2 mm, with lever, use with closer on leaf installation on the opposite hinge side	115193	silver-coloured	448.5 x 30.5 x 20.5 mm	4042938151931

TS 5000 L SoftClose *

GUIDE RAIL TS 5000 / 3000

Standard guide rail with lever

Designation	Description	Ident-No.	Colour	Dimensions	Spindle extension
Guide rail TS 3/5000	Standard, with lever	015695	white RAL 9016	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000	Standard, with lever	000773	according to RAL	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000 *	Standard, with lever	067985	brass-coloured	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000	Standard, with lever	068221	silver-coloured	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000 *	Standard, with lever	068222	dark bronze	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000	Standard, with lever	014945	Stainless steel optic	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000	Standard, with lever	076490	black RAL 9005	448.5 x 30.5 x 20.5 mm	

GUIDE RAIL BG TS 5000 / 3000

Standard guide rail with lever, opposite hinge side

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	025655	silver-coloured	448.5 x 30.5 x 20.5 mm	4106030256557
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	025656	according to RAL	448.5 x 30.5 x 20.5 mm	4106030256564
Guide rail BG TS 3/5000 *	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	029403	dark bronze	448.5 x 30.5 x 20.5 mm	4106030294030
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	029404	white RAL 9016	448.5 x 30.5 x 20.5 mm	4106030294047
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	028732	Stainless steel optic	448.5 x 30.5 x 20.5 mm	4106030287322
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	198812	black RAL 9005	448.5 x 30.5 x 20.5 mm	4042938988124

TS 5000 L SoftClose *

CLOSER BODY TS 5000 L SOFTCLOSE *

For opposite hinge side EN 3-6 overhead door closer with guide rail with individually adjustable closing speed of 0-15° door opening angle

Designation	Description	Ident-No.	Colour	Closing force in accordance with EN 1154	Dimensions
TS 5000 L SoftClose door closer *	Closing force EN 3-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	191210	according to RAL	EN 3 - 6	287 x 47 x 60 mm
TS 5000 L SoftClose door closer *	Closing force EN 3-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	191272	Stainless steel optic	EN 3 - 6	287 x 47 x 60 mm
TS 5000 L SoftClose door closer *	Closing force EN 3-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	191211	white RAL 9016	EN 3 - 6	287 x 47 x 60 mm
TS 5000 L SoftClose door closer *	Closing force EN 3-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	191209	silver-coloured	EN 3 - 6	287 x 47 x 60 mm

T-STOP GUIDE RAIL BG TS 3000 / 5000

With opening restrictor and lever, opposite hinge side

Designation	Description	Ident-No.	Colour	Dimensions	EAN
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102368	according to RAL	452.5 x 33 x 30 mm	4042938023689
T-Stop guide rail BG TS 3/5000 *	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102367	Stainless steel	452.5 x 33 x 30 mm	4042938023672
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	108482	white RAL 9016	452.5 x 33 x 30 mm	4042938084826
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102366	silver-coloured	452.5 x 33 x 30 mm	4042938023665

TS 5000 L SoftClose *

T-STOP GUIDE RAIL TS 3000/ 5000

With opening restrictor and lever

Designation	Description	Ident-No.	Colour	Dimensions	EAN
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	108481	white RAL 9016	452.5 x 33 x 30 mm	4042938084819
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102364	Stainless steel	452.5 x 33 x 30 mm	4042938023641
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102365	according to RAL	452.5 x 33 x 30 mm	4042938023658
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102363	silver-coloured	452.5 x 33 x 30 mm	4042938023634

ACCESSORIES

COVER CAP DOOR CLOSER *

For TS 4000/5000, curved shape

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Cover cap door closer *	for TS 5000/TS 4000, semi-radial, can only be used for door leaf installation	092943	Polished stainless steel	337 x 51 x 72 mm	4106030929437
Cover cap door closer *	for TS 5000/TS 4000, semi-radial, can only be used for door leaf installation	092944	Satin stainless steel	337 x 51 x 72 mm	4106030929444

COVER CAP DOOR CLOSER *

For TS 4000/5000, rectangular shape

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Cover cap door closer *	for TS 5000 / TS 4000, square, can only be used for door leaf installation	092938	Polished stainless steel	298 x 51 x 72 mm	4106030929383
Cover cap door closer *	for TS 5000 / TS 4000, square, can only be used for door leaf installation	092939	Satin stainless steel	298 x 51 x 72 mm	4106030929390

TS 5000 L SoftClose *

COVER CAP DOOR CLOSER *

For TS 5000 (L)/TS 4000, can only be used for door leaf installation

Designation	Description	Ident-No.	Colour	Dimensions	Material
Cover cap door closer *	for TS 5000 / TS 5000 L / TS 4000, can only be used for door leaf installation	067726	white RAL 9016	298 x 55 x 67.2 mm	
Cover cap door closer *	for TS 5000 / TS 5000 L / TS 4000, can only be used for door leaf installation	072696	Stainless steel	298 x 55 x 67.2 mm	Stainless steel
Cover cap door closer *	for TS 5000 / TS 5000 L / TS 4000, can only be used for door leaf installation	067724	silver-coloured	298 x 55 x 67.2 mm	
Cover cap door closer *	for TS 5000 / TS 5000 L / TS 4000, can only be used for door leaf installation	000756	according to RAL	298 x 55 x 67.2 mm	
Cover cap door closer *	for TS 5000 / TS 5000 L / TS 4000, can only be used for door leaf installation	067725	dark bronze	298 x 55 x 67.2 mm	

MECHANICAL HOLD-OPEN UNIT

For standard/T-Stop/Boxer 20.7 mm guide rail

Designation	Description	Ident-No.	Material	EAN
Mechanical hold-open unit	for standard / T-Stop / Boxer 20.7 mm guide rail, retention force adjustable, can be switched on and off, can be overridden	071924	Steel	4106030719243

FLEXIBLE OPENING RESTRICTOR

For riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail

Designation	Description	Ident-No.	Dimensions	Material	EAN
Flexible opening restrictor	For riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail	069780		Plastic	4106030697800

TS 5000 L SoftClose *

INSTALLATION MATERIAL

DRILLING TEMPLATE DOOR CLOSER

for TS 5000/TS 4000/TS 3000/TS 2000

Designation	Description	Ident-No.	Material	EAN
Drilling template door closer	for TS 5000/TS 4000/TS 3000/TS 2000	053134	Plastic	4106030531340

MOUNTING PLATE DOOR CLOSER *

For TS 5000 and TS 4000 with hole pattern in accordance with DIN EN 1154 Supplement 1

Designation	Description	Ident-No.	Material	EAN
Mounting plate *	for TS 5000/TS 4000 with hole pattern according to DIN EN 1154 Supplement 1	083992	Aluminum	4106030839927

MOUNTING PLATE GUIDE RAIL BG

For standard, ECline, T-Stop and EFS guide rail, opposite hinge side

Designation	Description	Ident-No.	Colour	Material	EAN
Mounting plate guide rail BG	for standard / ECline / T-Stop / EFS guide rail	124684	according to RAL	Aluminum	4042938246842
Mounting plate guide rail BG	for standard / ECline / T-Stop / EFS guide rail	124683	silver-coloured	Aluminum	4042938246835

TS 5000 L SoftClose *

MOUNTING PLATE DOOR CLOSER

For TS 5000 and TS 4000 with hole pattern in accordance with DIN EN 1154 Supplement 1

Designation	Description	Ident-No.	Colour	Dimensions	Material
Mounting plate door closer	for TS 5000/TS 4000 with hole pattern according to DIN EN 1154 Supplement 1	068627	white RAL 9016		Aluminum
Mounting plate door closer *	for TS 5000/TS 4000 with hole pattern according to DIN EN 1154 Supplement 1	057956	Galvanised		Aluminum
Mounting plate door closer	for TS 5000/TS 4000 with hole pattern according to DIN EN 1154 Supplement 1	029176	according to RAL		Aluminum
Mounting plate door closer	for TS 5000/TS 4000 with hole pattern according to DIN EN 1154 Supplement 1	049185	silver-coloured		Aluminum
Mounting plate door closer	for TS 5000/TS 4000 with hole pattern according to DIN EN 1154 Supplement 1	137725	Stainless steel optic		Aluminum
Mounting plate door closer	for TS 5000/TS 4000 with hole pattern according to DIN EN 1154 Supplement 1	052351	dark bronze		Aluminum
Mounting plate door closer	for TS 5000/TS 4000 with hole pattern according to DIN EN 1154 Supplement 1	076508	black RAL 9005		Aluminum

LINTEL CASING BRACKET

For standard guide rail

Designation	Description	Ident-No.	Colour	EAN
Lintel casing bracket *	For standard guide rail	030033	dark bronze	4106030300335
Lintel casing bracket *	For standard guide rail	028393	Stainless steel optic	4106030283935
Lintel casing bracket	For standard guide rail	025657	silver-coloured	4106030256571
Lintel casing bracket	For standard guide rail	025658	according to RAL	4106030256588
Lintel casing bracket	For standard guide rail	030034	white RAL 9016	4106030300342

TS 5000 L SoftClose *

LINTEL CASING BRACKET

For ECline and T-Stop guide rail

Designation	Description	Ident-No.	Colour	EAN
Lintel casing bracket	For ECline and T-Stop guide rail	115006	silver-coloured	4042938150064
Lintel casing bracket	For ECline and T-Stop guide rail	115007	according to RAL	4042938150071

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.