

Product data sheet

Slimchain 230 V *



Chain drive in an attractive design with numerous possible applications in 230 V version

AREAS OF APPLICATION

- Natural ventilation in the façade area
- Inward- and outward-opening windows with bottom-hung, top-hung and side-hung leaves
- Outward opening projected top hung windows
- Installation on wooden, PVC or metal windows
- Leaf, frame or integrated installation

**PRODUCT FEATURES**

- Can be integrated perfectly into the façade design thanks to its slim and discreet look
- Fast and easy installation with the Smart fix installation system
- Direct 230 V connection of the drive via a connection terminal with cable plug
- Concealed 230 V line-feed
- Direct access to the electronics for parameter setting via service cover
- Drive stroke with variable adjustment
- Available as special version – stroke, cable length, colour and left/right alignment configurable

TECHNICAL DATA

Productname	Slimchain 230 V *
Dimensions	25 x 44 mm
Space needed on frame (min.)	Frame installation inward-opening: 40 mm, leaf installation inward-opening: 16/21 mm, frame installation outward-opening: 31 mm
Space requirement on leaf (min.)	Frame installation inward-opening: 40 mm, leaf installation inward-opening: 34/29 mm, frame installation outward-opening: 19 mm
Opening speed ventilation	5 mm/s
Closing speed (max.)	5 mm/s
Force of pressure (max.)	100 N (depending on stroke), see force-path chart
Holding force (max.)	2000 N
Tensile force	300 N
Leaf weight	200 kg*
Overlap range	0 - 23 mm (depending on the application and bracket set)
Voltage at operation	230 V ± 10 %
Operating voltage	230 V
Current consumption	0.3 A
Power consumption	30 W
Duty rating	30 %
Special length of connector cable	5 m, 7.5 m
Min. core cross section	0.75 mm ²
Number of cores	3 cores
Service temperature	-5 - 70 °C
IP rating	IP30
protection rating	II
Adjustable opening speed (ventilation)	Yes
Type of stroke shortening	Synchronising unit, Factory setting
End position cut-off extended	electronic, via internal path sensor
End position cut-off retracted	electronically via current consumption
Overload cut-off	Yes
KNX ability	No



Bottom-hung window INWARD-opening frame installation	Yes
Bottom-hung window INWARD-opening leaf installation	Yes
Bottom-hung window OUTWARD-opening frame installation	Yes
Side-hung window INWARD-opening frame installation	Yes
Side-hung window INWARD-opening door leaf installation	Yes
Side-hung window OUTWARD-opening frame installation	Yes
Top-hung window INWARD-opening frame installation	Yes
Top-hung window INWARD-opening leaf installation	Yes
Top-hung window OUTWARD-opening frame installation	Yes
Projected top-hung window OUTWARD-opening frame installation	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Stroke	Length
Slimchain R		182590	EV1	500 mm	628 mm
Slimchain L		182570	EV1	200 mm	478 mm
Slimchain L		182593	white RAL 9016	800 mm	778 mm
Slimchain R		182582	EV1	200 mm	478 mm
Slimchain L		182584	EV1	300 mm	528 mm
Slimchain R		182591	white RAL 9016	500 mm	628 mm
Slimchain L		182571	white RAL 9016	200 mm	478 mm
Slimchain R		182595	white RAL 9016	800 mm	778 mm
Slimchain - special version	Can be configured: Stroke, cable length, colour, version L/R	182596	according to RAL		
Slimchain L		182588	EV1	500 mm	628 mm
Slimchain L		182585	white RAL 9016	300 mm	528 mm
Slimchain L		182592	EV1	800 mm	778 mm
Slimchain R		182586	EV1	300 mm	528 mm
Slimchain R		182594	EV1	800 mm	778 mm
Slimchain R		182587	white RAL 9016	300 mm	528 mm
Slimchain R		182583	white RAL 9016	200 mm	478 mm
Slimchain L		182589	white RAL 9016	500 mm	628 mm

ACCESSORIES

SAFETY SCISSORS NO. 35

For protection of bottom-hung leaves



Designation	Description	Ident-No.	Colour
Safety scissors no. 35	Fix pack available from stock (10 pieces), minimum leaf height 300mm	014499	Galvanised

SAFETY SCISSORS NO. 60

For protection of bottom-hung leaves



Designation	Description	Ident-No.	Colour
Safety scissors no. 60	Fix pack available from stock (10 pieces), minimum leaf height 700mm	133814	Galvanised

BRACKET SET A SLIMCHAIN

For bottom-hung, side-hung and top-hung windows



Designation	Description	Ident-No.	Colour
Bracket set A Slimchain	For bottom-hung, side-hung and top-hung windows, frame installation INWARD OPENING	147061	white RAL 9016
Bracket set A Slimchain	For bottom-hung, side-hung and top-hung windows, frame installation INWARD OPENING	147060	black

BRACKET SET B SLIMCHAIN

For bottom-hung, side-hung and top-hung windows



Designation	Description	Ident-No.	Colour
Bracket set B Slimchain	For bottom-hung, side-hung and top-hung windows, leaf installation INWARD OPENING and frame installation OUTWARD OPENING	147063	white RAL 9016
Bracket set B Slimchain	For bottom-hung, side-hung and top-hung windows, leaf installation INWARD OPENING and frame installation OUTWARD OPENING	147062	black

BRACKET SET C SLIMCHAIN

For bottom-hung and side-hung windows



Designation	Description	Ident-No.	Colour
Bracket set C Slimchain	For bottom-hung and side-hung windows, frame installation integrated INWARD OPENING	155878	silver-coloured

CHOICE OF BRACKETS FOR SLIMCHAIN

Special version can be configured in terms of opening type and colour




Designation	Description	Ident-No.	Colour
Bracket set Slimchain special version	Can be configured: Type of opening, colour	147071	according to RAL



LIN PARAMETER SETTING ADAPTER

Enables the connection of the GEZE ST 220 service terminal to the GEZE Slimchain 230 V chain drive for parameter setting via LIN-BUS



Designation	Description	Ident-No.
LIN parameter setting adapter	Enables the connection of the GEZE ST 220 service terminal to the GEZE Slimchain 230 V chain drive for parameter setting via LIN-BUS	179238

LTA-LSA *

Vent switch with rotary knob for OPEN / CLOSE



Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
LTA-LSA vent switch *	with rotary knob, can be used as "open-close" vent switch or stay-put as vent switch "open-stop-close"	118476	alpine white	80 x 80 mm	Flush-mounted installation

WRM-230 *

Receiving module for activating window drives with 230 V DC



WTH *

Remote control for activating GEZE automatic doors and window drives via the GEZE wireless programme



Designation	Description	Ident-No.	Dimensions	Operating voltage	Type of installation
WTH-2 remote control 2 channel *	with wall fixing and IP rating IP54	131210	78 x 51 x 15 mm	12 V DC	Wall
WTH-4 remote control 4 channel *	with wall fixing and IP rating IP54	131211	78 x 51 x 15 mm	12 V DC	Wall
WTH-1 remote control 1 channel *	with wall fixing and IP rating IP54	131209	78 x 51 x 15 mm	12 V DC	Wall

WTM *

Transmitting module for activating GEZE automatic doors and window drives via the GEZE wireless programme



Designation	Description	Ident-No.	Dimensions	Operating voltage	Type of installation
WTM transmitting module *	44 x 30 x 11 mm (W x H x D), for optional integration in push button	131212	44 x 30 x 11 mm	3 V DC	Integrated

WRM-230B *

Receiving module for activating window drives with 230 V DC



* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.