

Product data sheet

TS 1500 G *



Overhead door closer with guide rail with a leaf width of up to 750 mm

AREAS OF APPLICATION

- Right and left single-action doors
- Single-action doors up to 750 mm leaf width
- Door leaf installation hinge side and transom installation opposite hinge side

PRODUCT FEATURES

- Fixed closing force of EN1
- Can be used for right and left hand doors without conversion
- Hydraulic latching action which accelerates the door shortly before it is closed
- Closing speed can be individually adjusted
- All functions can be set from the front (except for closing force)

TECHNICAL DATA

Productname	TS 1500 G *
Leaf width (max.)	750 mm
Type of installation	Door leaf installation hinge side, Transom installation opposite hinge side
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Position of closing force adjustment	At the side
Hold-open function	Optional
Smoke switch integrated	No

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	DIN direction	Leaf width (max.)
GEZE TS 1500 G *	With guide rail and hold-open function	N/A	white RAL 9016	left / right	750 mm
GEZE TS 1500 G *	With guide rail and hold-open function	N/A	dark bronze	left / right	750 mm
GEZE TS 1500 G *	With guide rail and hold-open function	N/A	according to RAL	left / right	750 mm
GEZE TS 1500 G *	With guide rail and hold-open function	N/A	silver-coloured	left / right	750 mm

PART**GUIDE RAIL TS 1500 G**

with lever



Designation	Description	Ident-No.	Colour	Dimensions
Guide rail TS 1500 G	with lever	101887	white RAL 9016	390 x 30.5 x 20.5 mm
Guide rail TS 1500 G	with lever	101888	according to RAL	390 x 30.5 x 20.5 mm
Guide rail TS 1500 G	with lever	101885	silver-coloured	390 x 30.5 x 20.5 mm

CLOSER BODY TS 1500 G *

Main body for overhead door closer with guide rail EN 1



Designation	Description	Ident-No.	Colour	Closing force in accordance with EN 1154	Dimensions
GEZE TS 1500 G closer *	Size EN 1 (without guide rail and lever)	N/A	silver-coloured	EN 1	177 x 39 x 50 mm
GEZE TS 1500 G closer *	Size EN 1 (without guide rail and lever)	N/A	white RAL 9016	EN 1	177 x 39 x 50 mm
GEZE TS 1500 G closer *	Size EN 1 (without guide rail and lever)	N/A	according to RAL	EN 1	177 x 39 x 50 mm
GEZE TS 1500 G closer *	Size EN 1 (without guide rail and lever)	N/A	dark bronze	EN 1	177 x 39 x 50 mm

ACCESSORIES**COVER CAP DOOR CLOSER**

For TS 1500, can only be used for door leaf installation



Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer	For TS 1500, can only be used for door leaf installation	080147	silver-coloured	188 x 47 x 57.5 mm
Cover cap door closer	For TS 1500, can only be used for door leaf installation	080149	white RAL 9016	188 x 47 x 57.5 mm
Cover cap door closer *	For TS 1500, can only be used for door leaf installation	080148	dark bronze	188 x 47 x 57.5 mm

MECHANICAL HOLD-OPEN UNIT

For standard/T-Stop/Boxer 20.7 mm guide rail



Designation	Description	Ident-No.
Mechanical hold-open unit	for standard / T-Stop / Boxer 20.7 mm guide rail, retention force adjustable, can be switched on and off, can be overridden	071924

FLEXIBLE OPENING RESTRICTOR

for riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail



Designation	Description	Ident-No.	Dimensions
Flexible opening restrictor	for riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail	069780	

INSTALLATION MATERIAL**MOUNTING PLATE GUIDE RAIL ***

For TS 1500 G



Designation	Description	Ident-No.	Colour
Mounting plate guide rail	For TS 1500 G	072355	according to RAL
Mounting plate guide rail	For TS 1500 G	072333	silver-coloured

MOUNTING PLATE DOOR CLOSER

for TS 1500



Designation	Description	Ident-No.	Colour
Mounting plate door closer	for TS 1500	029683	dark bronze
Mounting plate door closer	for TS 1500	029682	silver-coloured
Mounting plate door closer	for TS 1500	029685	white RAL 9016
Mounting plate door closer	for TS 1500	029686	according to RAL

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.