Product data sheet

Levolan 60 complete set

Levolan sliding door fitting for leaf weights up to 60 kg

AREAS OF APPLICATION

- For leaf weights up to 60 kg
- For glass elements toughened safety glass 8, 10 and 12 mm as well as laminated safety glass up to 10 mm (with additional LSG kit) and timber leaves up to a weight of 60 kg
- For wall and ceiling installation
- Suitable for interior use

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-11-07T03:57:12Z

Levolan 60 complete set

PRODUCT FEATURES

→ Design sliding door fitting for glass and timber leaves

TECHNICAL DATA

Productname	Levolan 60 complete set
Leaf material	Glass, Plastic, Metal, Wood
Leaf weight (max.)	60 kg
Leaf weight (max.) with draw-in damper	60 kg
Number of leaves	1-leaf, 2-leaf
Leaf width (min.)	400 mm
Leaf width (max.)	1240 mm
Test cycles	100000
Corrosion protection class	3
Pane thickness	8 - 12 mm
Type of installation	Wall, Ceiling
Side panel	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions	Leaf width (min.)
Levolan 60 complete set	For wall and ceiling installation	147169	Stainless steel optic	2450 mm	400 mm
Levolan 60 complete set	For wall and ceiling installation	147166	EV1	2450 mm	400 mm
Levolan 60 complete set	For wall and ceiling installation	147167	Stainless steel optic	1650 mm	400 mm
Levolan 60 complete set	For wall and ceiling installation	147164	EV1	1650 mm	400 mm
Levolan 60 complete set	For wall and ceiling installation	147165	EV1	2050 mm	400 mm
Levolan 60 complete set	For wall and ceiling installation	147168	Stainless steel optic	2050 mm	400 mm

Levolan 60 complete set

ACCESSORIES

LEVOLAN SOFTSTOPDUO SET, DAMPED ON BOTH SIDES, UP TO 100 KG

Levolan SoftStopDuo draw-in damping on both sides for leaf weights up to 100 kg

Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)	Leaf weight (max.)
Levolan SoftStopDuo set, damped on both sides, up to 100 kg	for draw-in damping left right, consisting of; 1 x double damping unit, 2 x spacers - Levolan 60 and 2 x spacers - Levolan 120 for cover panel bracket, 2 x adjustable triggers, can also be retrofitted - for Levolan 60 minimum leaf width 770 mm, for Levolan 120 minimum leaf width 1010 mm	146402	770 mm	1240 mm	100 kg

LEVOLAN 60 SOFTSTOP SET, DAMPED ON ONE SIDE, UP TO 60 KG

Levolan SoftStop one-sided draw-in damping left-hand version

Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)	Leaf weight (max.)
Levolan 60 SoftStop set, damped on one side, up to 60 kg	For draw-in damping on the left, consisting of: 1 x damping unit, 1 x distance piece for cover panel bracket, 1 x trigger, can also be retrofitted – minimum leaf width 570 mm	146370	570 mm	1240 mm	60 kg

LEVOLAN 60 SOFTSTOP SET, DAMPED ON ONE SIDE, UP TO 60 KG

Levolan SoftStop draw-in damping on one side right version

Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)	Leaf weight (max.)
Levolan 60 SoftStop set, damped on one side, up to 60 kg	for draw-in damping right, consisting of: 1 x damping unit, 1 x spacer for cover panel bracket, 1 x trigger, can also be retrofitted - minimum leaf width 570 mm	146401	570 mm	1240 mm	60 kg

Levolan 60 complete set

SPACER PROFILE FOR WALL CLEARANCE LEVOLAN 60 / 120

Spacer profile for wall installation of Levolan 60/120

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	157993	Stainless steel optic	2850 mm	4042938579933
Spacer profile for wall clearance Levolan 60 / 120 *	10 mm additional space, can be stacked up to 20 mm	147571	Stainless steel optic	2450 mm	4042938475716
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147557	EV1	2450 mm	4042938475570
Spacer profile for wall clearance Levolan 60 / 120 *	10 mm additional space, can be stacked up to 20 mm	147559	Stainless steel optic	1650 mm	4042938475594
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147572	Stainless steel optic	6000 mm	4042938475723
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147558	EV1	6000 mm	4042938475587
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm / bespoke configuration	147573			4042938475730
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	157991	EV1	2850 mm	4042938579919
Spacer profile for wall clearance Levolan 60 / 120 *	10 mm additional space, can be stacked up to 20 mm	147560	Stainless steel optic	2050 mm	4042938475600
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147556	EV1	2050 mm	4042938475563
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147555	EV1	1650 mm	4042938475556

CLAMPING PROFILE FOR ATTACHING WOODEN / METAL LEAVES

Clamping profile for connecting timber leaves and Levolan 60/120 roller carriage

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Clamping profile for attaching wooden / metal leaves	for the attachment of door leaves made of wood / metal / plastic to Levolan 60 / 120	146958	EV1	1500 mm	4042938469586
Clamping profile for attaching wooden / metal leaves	for the attachment of door leaves made of wood / metal / plastic to Levolan 60 / 120	146957	EV1	1000 mm	4042938469579

Levolan 60 complete set

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Clamping profile for attaching wooden / metal leaves	Bespoke	146959	EV1		4042938469593

FLOOR GUIDE SET GLASS GUIDE

Floor guide for glass sliding leaves for glass thickness 8, 10 and 12 mm

Designation	Description	Ident-No.	Colour	Pane thickness	EAN
Floor guide for glass leaf (stainless steel)	For 8, 10, 12 mm glass	134990	Stainless steel	8 – 12 mm	4042938349901

FLOOR GUIDE FOR WOODEN LEAF

Floor guide for wooden leaves mounted on the floor

Designation	Description	Ident-No.	Colour	EAN
Floor guide for timber leaf standard	Without attachment material	002191	Galvanised	4106030021919

FLUSH PULL, ANGULAR *

Stainless steel shell in rectangular design 128 x 82 mm

Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
Flush pull, angular	Stainless steel shell in rectangular design 128 x 82 mm	169808	Satin stainless steel	128 x 82 x 20 mm	Door leaf installation

Levolan 60 complete set

FLUSH PULL, OVAL *

Stainless steel shell in oval design 40 x 120 mm

Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
Flush pull, oval	Stainless steel shell in oval design 40 x 120 mm	169809	Satin stainless steel	120 x 40 x 14.5 mm	Door leaf installation

FLUSH PULL, ROUND *

Stainless steel shell in round design, 65 mm diameter

Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
Flush pull, round	Stainless steel shell in round design, 65 mm diameter	169810	Satin stainless steel	16 mm	Door leaf installation

HANDLE RING, GLASS *

Stainless steel operating device for all-glass door leaes

Designation	Description	Ident-No.	Colour	Dimensions	Pane thickness
Handle ring, glass	Handle ring for pane thickness 10 - 12 mm, 58 mm outer diameter	169811	Satin stainless steel	26 mm	10 - 12 mm

Levolan 60 complete set

PULL HANDLE D-SHAPE *

Stainless steel pull handle pair

Designation	Description	Ident-No.	Colour	Pane thickness	Type of installation
Pull handle D-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 22 mm; hole spacing: 300 mm	169819	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation
Pull handle D-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 19 mm; hole spacing: 200 mm	169818	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation
Pull handle D-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 19 mm; hole spacing: 150 mm	169817	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation
Pull handle D-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 25 mm; hole spacing: 300 mm	169820	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation

PULL HANDLE H-SHAPE

Stainless steel pull handle pair

Designation	Description	Ident-No.	Colour	Pane thickness	Type of installation
Pull handle H-shape	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 25 mm; hole spacing: 300 mm; total length: 400 mm	169822	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation
Pull handle H-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 25 mm; hole spacing: 250 mm; total length: 350 mm	169821	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation
Pull handle H-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 32 mm; hole spacing: 600 mm; total length: 800 mm	169823	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation
Pull handle H-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - dDiameter: 32 mm; hole spacing: 1200 mm; total length: 1400 mm	169824	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation

Levolan 60 complete set

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.