Product data sheet

# ECdrive T2 eco drive *



Automatic linear sliding door drive for doors with up to 100 kg leaf weight

## AREAS OF APPLICATION

- Single and double leaf sliding door systems
- Interior and exterior doors with moderate usage
- Opening widths from 700 to 2200 mm possible
- Suitable profile systems are fine-framed profile systems with ISO and mono glass, toughened safety glass clamping profile, on-site frame and wooden leaves

**GEZE GmbH** | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com

2026-11-07T04:18:55Z

# ECdrive T2 eco drive *

## PRODUCT DESCRIPTION

The ECdrive T2 eco offers a sleek design for a wide range of configuration options and is particularly easy to commission thanks to its reduced functions. Eco mode minimises the energy consumption of activation and safety sensors and ensures efficient and sustainable operation.

## PRODUCT FEATURES

- Simplified commissioning and parameter setting thanks to reduced functional properties
- Eco mode permanently active to reduce the power consumption of activation and safety sensors in hold open, night mode, and off modes of operation
- Efficient installation thanks to pre-drilled tracks and elongated holes
- Profile lengths of the track and cover optimised for the application, measuring 2600 mm and 4500 mm respectively
- Integrated cable routings make cable laying easier
- Independent error recognition and recording
- Configurable output for error transmission
- Integrated rechargeable battery for continued operation during power failures for a maximum of 30 minutes or 30 cycles
- Self-cleaning roller carriage reduces maintenance effort and costs
- Electric toothed belt locking available as an option

## TECHNICAL DATA

| | ECdrive T2 eco drive * |
|---|---|
| Height | 100 mm |
| Depth | 190 mm |
| Service temperature | -15 - 50 °C |
| Self-learning | Yes |
| Pharmacy opening | No |
| Interlocking door system function | No |

## VARIANTS / ORDER INFO

| Designation | Description | Ident-No. | Colour | Supply voltage | Dimensions |
|---|---|---|---|---|---|
| ECdrive T2 eco drive, length: 3100 mm * | Drive system for linear sliding doors in high traffic areas | 210297 | EV1 | | 3100 x 100 x 190 mm |
| ECdrive T2 eco drive, length: 4400 mm * | Drive system for linear sliding doors in high traffic areas | 210296 | EV1 | | 4100 x 100 x 190 mm |
| ECdrive T2 eco drive, length: 2200 mm * | Drive system for linear sliding doors in high traffic areas | 210298 | EV1 | | 2100 x 100 x 190 mm |

# ECdrive T2 eco drive *

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.