Product data sheet

Tubular frame strike box *

Mechanical strike box as passive leaf rod locking element on double leaf doors

AREAS OF APPLICATION

- Passive leaf locking element (rod locking) on double leaf tubular-framed doors
- Location for vertical rods from above and below
- Can be used on fire protection doors
- Automated passive leaf unlocking possible through combination with IQ AUT

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-11-14T03:48:31Z

Tubular frame strike box *

PRODUCT FEATURES

- → Mechanical self-locking via top lock
- → Unlocking of active leaf via passive leaf door fitting (full panic function)

TECHNICAL DATA

Productname	Tubular frame strike box *
DIN direction	left / right

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	DIN direction	Backset	EAN
Strike box tubular-framed doors, short *	Without face plate, distance of the screw points for locking bolts: 267 mm / the vertical locking bolts are positioned on backset	152249	left / right	45 mm	4042938522496
Strike box tubular-framed doors, short *	Without face plate, distance of the screw points for locking bolts: 267 mm / the vertical locking bolts are positioned on backset	152251	left / right	70 mm	4042938522519
Strike box tubular-framed doors, short *	Without face plate, distance of the screw points for locking bolts: 267 mm / the vertical locking bolts are positioned on backset	152248	left / right	35 mm	4042938522489
Strike box tubular-framed doors, short *	Without face plate, distance of the screw points for locking bolts: 267 mm / the vertical locking bolts are positioned on backset	152250	left / right	60 mm	4042938522502

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.