Product data sheet

R guide rail TS 5000 *



with integrated smoke switch control unit and lever, without electric hold-open device

AREAS OF APPLICATION

- Single leaf doors
- Hold-open systems with integrated smoke switch
- For combination with a free swing door closer or hold-open magnet
- Installation on hinge side
- Right and left single-action doors

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-10-31T05:34:15Z

R guide rail TS 5000 *

PRODUCT FEATURES

- Integrated smoke switch control unit
- Smoke switch with contamination indicator and adaption of the alarm threshold
- Additional smoke detectors can be fitted
- Operating voltage 230 V AC
- Horizontally adjustable in the installation position by 4 mm through elongated holes
- With screwed slide block

TECHNICAL DATA

Productname	R guide rail TS 5000 *
Supply voltage	230 V AC
Input voltage	230 V AC
Frequency of supply voltage	50/60 Hz
Duty rating	100 %
IP rating	IP20
Approvals	General building approval from DIBt as a hold-open system
Length	745 mm
Width	55 mm
Height	30 mm
Free swing function on active leaf	No
opening restrictor upgradable	Yes
Hold-open function	Optional
Smoke switch integrated	Yes
Visual status display	Yes
Contamination indicator	Yes
Adaption of the alarm threshold	Yes
Integrated power supply	Yes
Height correction possible	Yes
Flexible opening restrictor	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Supply voltage	Dimensions
R guide rail TS 5000 *	with integrated smoke switch control unit and lever, without electric hold-open device	167813	silver-coloured	230 V AC	745 x 55 x 30 mm
R guide rail TS 5000 *	with integrated smoke switch control unit and lever, without electric hold-open device	167815	Stainless steel optic	230 V AC	745 x 55 x 30 mm
R guide rail TS 5000 *	with integrated smoke switch control unit and lever, without electric hold-open device	167814	according to RAL	230 V AC	745 x 55 x 30 mm

R guide rail TS 5000 *

ACCESSORIES

FLEXIBLE OPENING RESTRICTOR

For E and R guide rails, 1- and 2-leaf



Designation	Description	Ident-No.	Material	EAN
Flexible opening restrictor	for guide rail 1-leaf: TS 5000 E/R/RFS (door leaf installation), Boxer E; 2-leaf: all E/R/ISM variants TS 5000 (incl. VPK) and Boxer	145311	Plastic	4042938453110

INSTALLATION MATERIAL

MOUNTING PLATE GUIDE RAIL *

For R and RFS guide rail



Designation	Description	Ident-No.	Colour	Material	EAN
Mounting plate guide rail *	for R / RFS-guide rail	123296	silver-coloured	Aluminum	4042938232968
Mounting plate guide rail *	for R / RFS-guide rail	123297	according to RAL	Aluminum	4042938232975

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.