Product data sheet

Power supply NT 2.5 A-24 V HS *

24 V power supply for top hat rail mounting

AREAS OF APPLICATION

- For installation on top-hat rails
- For the supply of 24 V drives and control units

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-11-07T04:17:10Z

Power supply NT 2.5 A–24 V HS *

PRODUCT FEATURES

- Fast and simple installation
- Powerful power supply with small dimensions

TECHNICAL DATA

	Power supply NT 2.5 A-24 V HS *
Dimensions	52 x 90 x 58 mm
Output voltage	24 V DC
Output current (max.)	2.5 A
Operating voltage	230 V
Material	Plastic

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions	Operating voltage
Power supply NT 2.5 A-24 V HS *	Output voltage 24 V DC, W x H x D: 52 x 90 x 58 mm, assembly on top hat rail, 3 horizontal pitches	151424	black	52 x 90 x 58 mm	230 V

ACCESSORIES

SURFACE-MOUNTED HOUSING *

Housing for surface mounting of top hat rail components such as power supply units or control units

Designation	Description	Ident-No.	Colour	Dimensions	IP rating
Surface-mounted housing *	Size: W x H x D = 193 x 130 x 82 mm. For electronic top hat rail components, e.g. power supply units	152010	white	193 x 130 x 82 mm	IP40

Power supply NT 2.5 A–24 V HS *

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.