

Certificate of Constancy of Performance



Certificate No.: 0757-CPR-229PANIK-7013137-5-11

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 179:2008-01

Emergency exit devices

Emergency exit devices operated by a lever handle for single and double leaf doorsets "IQ lock"

Product description/
specification

According to configuration in **annex 1**

Levels and classes of
performance

According to configuration in **annex 1**

Intended use(s)

Intended for use on doors in escape routes with requirements for fire resistance and smoke control

placed on the market
under the name or trade
mark of

GEZE GmbH

Reinhold-Vöster-Str. 21-29, DE-71229 Leonberg

and produced in the
manufacturing plant(s)

6039631 + 8003725

Notified body No.

0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 179 : 2008

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.


This certificate was first issued on 09.09.2009 and will remain valid until 11.10.2027, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the ift Rosenheim no. 229PANIK 7013137.



Pascal Geiger

Pascal Geiger
Deputy head of the notified product certification body
Certification & Surveillance Body
ift Rosenheim
17.04.2026



www.ec.europa.eu

Identity check



www.ift-rosenheim.de/ift-zertifiziert

ID: 2EE-69C5B

Certificate of constancy of performance

Annex 1 Page 1 of 4
Certificate holder: GEZE GmbH
Date of issue: 17.04.2026



Certificate No.: 0757-CPR-229PANIK-7013137-5-11

Emergency exit devices as per EN 179 : 2008 for single and double leaf doorsets:

Classification:	3	7	7	B	1	3	4	2	A	A/B
------------------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	------------

Intended use: Intended for use on doors in escape routes with requirements for fire protection and smoke control

Test report: No. 207 41088 of 08 September 2009
Test report: No. 207 36801 of 12 February 2009
Test report: No. 120001894.20 of 29 December 2006 (MPA)
Test report: No. 120001894.21 of 29 December 2006 (MPA)
Test report: No. 120003909 of 27 January 2012 (MPA)
Test report: No. 13-001273-PR01 of 14 May 2013
Test report: No. 271 35385 Rev 1 of 29 April 2008
Test report: No. 271 38194 of 27 May 2009
Test report: No. 13-000685-PR03 of 05 July 2013
Test report: No. 13-000685-PR04 of 05 July 2013
Result protocol: No. 12-000623-PR06 of 28 August 2012
Result protocol: No. 14-003403-PR03 of 11 June 2015
Result protocol: No. 14-003403-PR04 of 11 June 2015

Certificate of constancy of performance

Annex 1 Page 2 of 4
 Certificate holder: GEZE GmbH
 Date of issue: 17.04.2026



Certificate No.: 0757-CPR-229PANIK-7013137-5-11

Emergency exit devices:

Function	Designation	Type of device	Backsets	Distance	Face plate	Strike plate	Hole
I	IQ lock M IQ lock M DL	A	35 mm to 100 mm	72 mm to 94 mm	20 mm to 30 mm	Flat strike plate Corner strike plate Flap strike plate	Round cylinder and profile cylinder
I*	IQ lock C IQ lock C DL	A					
II	IQ lock EM IQ lock EM DL	A					
IM	IQ lock EL IQ lock EL DL	A					
IM*	IQ lock AUT	A					

In combination with:

Emergency exit device:

No.	Designation	Type of device	Backsets	Face plate	Accessory
1.	Strike box DL	A	35 mm to 100 mm	20 mm to 30 mm	133916
					133917
					133918
					133919
					133920
					133921
					133922
					134955
					135799
					153741
					156705
					156709
					156710
					156711
					156712
					156726
					157391
					161530
					161532
					161977
161978					
161980					
162310					
162311					
162322					
162323					
162324					
164102					

Certificate of constancy of performance

Annex 1 Page 3 of 4
 Certificate holder: GEZE GmbH
 Date of issue: 17.04.2026



Certificate No.: 0757-CPR-229PANIK-7013137-5-11

External and/or internal hardware furniture:

No.	Manufacturer	Type	Code
1.	FSB Franz Schneider Brakel GmbH & Co. KG	-/-	DO 20.3.01 DO 20.3.02
2.	HOPPE Holding AG	-/-	DO 20.5.01 DO 20.5.02 DO 20.7.01 DO 20.7.02 DO 20.20.01 DO 20.20.02
3.	HEWI Heinrich Wilke GmbH	162XAH11.530, 162XAH52.640, 111XAR11.110, 111R11.210, 111R11.230, 111R11.240	VE 30-26
4.	Grundmann Beschläge GmbH	1554FHA, 1754FHA, 2254FHA, 2454FHA, 2554NFHA	-/-
5.	ECO Schulte GmbH & Co. KG	D-116.AL, D-116.ER, D-335.ER	-/-
6.	KABA AG	elologic c-lever	-/-
7.	ASSA ABLOY (Schweiz) AG	-/-	5974 5978 5979
8.	Süd-Metall Beschläge GmbH	Paula-R FS	-/-
9.	Hermet Metallwaren GmbH	1801, 1801.FS, 1801.GK, 1801 R.FS, 1805; 1808, 1808.FS, 1808.GK, 1809, 1811, 1816	ift 235 8000244
10.	Meesenburg GmbH & Co. KG	BG RTG U-FORM OVALE ROS. 9MM AP BG RTG U-FORM GK OVALE ROS. 9MM AP BG RTG U-FORM 45° OV.ROS. 9MM AP BG RTG U-90°-FORM OV.ROS. 9MM AP BG RTG U-90°-FORM GK OV.ROS.9MM AP	-/-
11.	VIELER International KG	-/-	DO 20.12.01 DO 20.12.02
12.	KCC Door Hardware & Security	KF2001 KF5312	ift Rosenheim

Certificate of constancy of performance

Annex 1
Certificate holder: GEZE GmbH
Date of issue: 17.04.2026

Page 4 of 4



Certificate No.: 0757-CPR-229PANIK-7013137-5-11

Explanations:

Actuation type A:	Latches with "handle actuation"
Actuation type B:	Latches with "push plate actuation"
Area of application class A:	Outward-opening single-leaf escape door, double-leaf escape door: active or passive leaf
Area of application class B:	Single-leaf escape door opening outwards only
Area of application class C: Fixed leaf only	Double-leaf escape door opening outwards:
Area of application class D:	Single-leaf escape door opening inwards only
Description:	Self-locking mortise locks with escape door function (panic function) and split cross latch. The bolt is located in the center between the two latch parts.
Function I:	One-piece lock nut, permanently active escape door function from the inside. Opening from the inside is always possible via the interior fitting. From the outside, the door can be opened with the key via the changeover. * With additional feedback contacts integrated in the lock
Function II:	Split lock cylinder, permanently active escape door function from the inside. Opening from the inside is always possible via the interior fitting. The exterior fitting or the exterior half of the lock cylinder is electronically controlled to engage or disengage. A special fitting with a split pin is required.
Function IM:	One-piece lock nut, permanently active escape door function from the inside. The door can always be opened from the inside using the interior fitting. From the outside, the door can be opened using the key via the changeover. Motorized bolt drive. * Motorized unlocking of active and passive sashes
Lock cylinder:	All types of lock cylinders with a free-running function do not affect proper operation.