Product data sheet

Closer body TS 4000 E

Main body for overhead door closer with link arm EN 1-6 with electric hold-open device

AREAS OF APPLICATION

- Fire and smoke protection doors
- Right and left single-action doors
- Single-action doors up to 1400 mm leaf width
- Door leaf installation hinge side and transom installation opposite hinge side

Closer body TS 4000 E

PRODUCT FEATURES

- Closing force can be variably adjusted from the front
- Visual closing force display ensures correct setting
- Closing seed can be adjusted from the front via valve
- Latching action can be adjusted via link arm
- Electric hold-open device
- Door closer, can be used for right and left hand doors
- Supply voltage 24 V DC
- Same mounting hole pattern as all GEZE TS 4000 closers

TECHNICAL DATA

Productname	Closer body TS 4000 E
Closing force in accordance with EN 1154	EN 1 - 6
Leaf width (max.)	1400 mm
Type of installation	Door leaf installation hinge side
Opening angle (max.)	180 °
Identical design for DIN left and DIN right	Yes
Input voltage	24 V DC
Electrical power consumption	1 W
Duty rating	100 %
Residual ripple	20 %
IP rating	IP43
Standard conformity	EN 1154:1996/A1:2002/AC:2006, EN 1155
Suitability for fire protection doors	Yes
Length	325 mm
Width	46 mm
Height	60 mm
Closing force adjustable	Yes, stepless
Adjustable closing speed	Yes
Latching action adjustable	Yes, via link arm
Back check integrated	No
Position of closing force adjustment	Front
Visual closing force display	Yes
Safety valve againts overload	Yes
Thermo-control valves	Yes
Hold-open function	Electrical
Hold-open device can be overridden	Yes
Smoke switch integrated	No

Closer body TS 4000 E

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Closing force in accordance with EN 1154	Dimensions
GEZE TS 4000 E door closer	Closing force EN 1-6, door leaf installation hinge side, with electric hold-open device and connector box (without link arm)	105212	according to RAL	EN 1 - 6	325 x 46 x 60 mm
GEZE TS 4000 E door closer	Closing force EN 1-6, door leaf installation hinge side, with electric hold-open device and connector box (without link arm)	105211	silver-coloured	EN 1 - 6	325 x 46 x 60 mm