Product data sheet

TS 3000 EN 3

Overhead door closer with guide rail for single leaf doors with a leaf width up to 950 mm

AREAS OF APPLICATION

- Fire and smoke protection doors
- Right and left single-action doors
- Single-action doors up to 950 mm leaf width
- Door leaf installation hinge side
- Door leaf installation opposite hinge side

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com

2026-11-07T03:47:49Z

TS 3000 EN 3

PRODUCT FEATURES

- Fixed closing force of EN 3
- Can be used for right and left hand doors without conversion
- Hydraulic latching action which accelerates the door shortly before it is closed
- All functions can be adjusted from the front

TECHNICAL DATA

Productname	TS 3000 EN 3
Closing force in accordance with EN 1154	EN 3
Barrier-free in accordance with DIN 18040 up to leaf width (max.) in mm	950 mm
Leaf width (max.)	950 mm
Type of installation	Door leaf installation hinge side, Door leaf installation opposite hinge side
Opening angle (max.)	180 °
Suitability for fire protection doors	Yes
Closing force adjustable	No
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Back check integrated	No
Hold-open function	Optional
Smoke switch integrated	No

PART

CLOSER BODY TS 3000 EN 3 *

Main body for overhead door closer with guide rail EN3

Designation	Description	Ident-No.	Colour	Closing force in accordance with EN 1154	Dimensions
GEZE TS 3000 EN 3 Closer	Size EN 3 (without guide rail and lever)	102308	according to RAL	EN 3	226 x 46 x 60 mm
GEZE TS 3000 EN 3 Closer	Size EN 3 (without guide rail and lever)	102247	silver-coloured	EN 3	226 x 46 x 60 mm
GEZE TS 3000 EN 3 Closer	Size EN 3 (without guide rail and lever)	102306	dark bronze	EN 3	226 x 46 x 60 mm
GEZE TS 3000 EN 3 Closer	Size EN 3 (without guide rail and lever)	102307	white RAL 9016	EN 3	226 x 46 x 60 mm

TS 3000 EN 3

GUIDE RAIL TS 5000 / 3000

Standard guide rail with lever

Designation	Description	Ident-No.	Colour	Dimensions	Spindle extension
Guide rail TS 3/5000	Standard, with lever	015695	white RAL 9016	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000	Standard, with lever	000773	according to RAL	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000 *	Standard, with lever	067985	brass-coloured	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000	Standard, with lever	068221	silver-coloured	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000 *	Standard, with lever	068222	dark bronze	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000	Standard, with lever	014945	Stainless steel optic	448.5 x 30.5 x 20.5 mm	
Guide rail TS 3/5000	Standard, with lever	076490	black RAL 9005	448.5 x 30.5 x 20.5 mm	

GUIDE RAIL TS 5000 / 3000 VERTICALLY ADJUSTABLE *

With height compensation +/- 2 mm and lever

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Guide rail TS 3/5000 vertically adjustable	Height compensation +/- 2 mm, with lever	115191	silver-coloured	448.5 x 30.5 x 20.5 mm	4042938151917
Guide rail TS 3/5000 vertically adjustable *	Height compensation +/- 2 mm, with lever	115192	according to RAL	448.5 x 30.5 x 20.5 mm	4042938151924

GUIDE RAIL BG TS 5000 / 3000

Standard guide rail with lever, opposite hinge side

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	025655	silver-coloured	448.5 x 30.5 x 20.5 mm	4106030256557
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	025656	according to RAL	448.5 x 30.5 x 20.5 mm	4106030256564
Guide rail BG TS 3/5000 *	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	029403	dark bronze	448.5 x 30.5 x 20.5 mm	4106030294030

TS 3000 EN 3

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	029404	white RAL 9016	448.5 x 30.5 x 20.5 mm	4106030294047
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	028732	Stainless steel optic	448.5 x 30.5 x 20.5 mm	4106030287322
Guide rail BG TS 3/5000	Standard, with lever, use with door closer on leaf installation on the opposite hinge side	198812	black RAL 9005	448.5 x 30.5 x 20.5 mm	4042938988124

GUIDE RAIL BG TS 5000 / 3000 VERTICALLY ADJUSTABLE *

With height compensation +/- 2 mm, with lever, opposite hinge side

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Guide rail BG TS 3/5000 vertically adjustable *	Height compensation +/- 2 mm, with lever, use with closer on leaf installation on the opposite hinge side	115194	according to RAL	448.5 x 30.5 x 20.5 mm	4042938151948
Guide rail BG TS 3/5000 vertically adjustable *	Height compensation +/- 2 mm, with lever, use with closer on leaf installation on the opposite hinge side	115193	silver-coloured	448.5 x 30.5 x 20.5 mm	4042938151931

T-STOP GUIDE RAIL TS 3000/ 5000

With opening restrictor and lever

Designation	Description	Ident-No.	Colour	Dimensions	EAN
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	108481	white RAL 9016	452.5 x 33 x 30 mm	4042938084819
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102364	Stainless steel	452.5 x 33 x 30 mm	4042938023641
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102365	according to RAL	452.5 x 33 x 30 mm	4042938023658
T-Stop guide rail TS 3/5000	with integrated opening restrictor and lever	102363	silver-coloured	452.5 x 33 x 30 mm	4042938023634

TS 3000 EN 3

T-STOP GUIDE RAIL BG TS 3000 / 5000

With opening restrictor and lever, opposite hinge side

Designation	Description	Ident-No.	Colour	Dimensions	EAN
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102368	according to RAL	452.5 x 33 x 30 mm	4042938023689
T-Stop guide rail BG TS 3/5000 *	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102367	Stainless steel	452.5 x 33 x 30 mm	4042938023672
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	108482	white RAL 9016	452.5 x 33 x 30 mm	4042938084826
T-Stop guide rail BG TS 3/5000	with integrated opening restrictor and lever, use with door closer on leaf installation opposite hinge side or with pivot bearing in leaf and transom installation opposite hinge side	102366	silver-coloured	452.5 x 33 x 30 mm	4042938023665

ACCESSORIES

MECHANICAL HOLD-OPEN UNIT

For standard/T-Stop/Boxer 20.7 mm guide rail

Designation	Description	Ident-No.	Material	EAN
Mechanical hold-open unit	for standard / T-Stop / Boxer 20.7 mm guide rail, retention force adjustable, can be switched on and off, can be overridden	071924	Steel	4106030719243

TS 3000 EN 3

FLEXIBLE OPENING RESTRICTOR

For riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail

Designation	Description	Ident-No.	Dimensions	Material	EAN
Flexible opening restrictor	For riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail	069780		Plastic	4106030697800

COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, can only be used for door leaf installation

Designation	Description	Ident-No.	Colour	Dimensions	Material
Cover cap door closer *	For TS 3000/ TS 2000, can only be used for door leaf installation	072769	Stainless steel	239 x 56 x 69.2 mm	Stainless steel
Cover cap door closer *	For TS 3000/ TS 2000, can only be used for door leaf installation	072770	Brass	239 x 56 x 69.2 mm	Brass
Cover cap door closer *	For TS 3000/ TS 2000, can only be used for door leaf installation	013487	silver-coloured	239 x 56 x 69.2 mm	
Cover cap door closer *	For TS 3000/ TS 2000, can only be used for door leaf installation	014855	white RAL 9016	239 x 56 x 69.2 mm	
Cover cap door closer *	For TS 3000/ TS 2000, can only be used for door leaf installation	014849	dark bronze	239 x 56 x 69.2 mm	
Cover cap door closer *	For TS 3000/ TS 2000, can only be used for door leaf installation	014856	according to RAL	239 x 56 x 69.2 mm	

COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, curved shape

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Cover cap door closer *	for TS 3000/TS 2000, semi-radial, can only be used for door leaf installation	092928	Polished stainless steel	277 x 54 x 72 mm	4106030929284
Cover cap door closer *	for TS 3000/TS 2000, semi-radial, can only be used for door leaf installation	092929	Satin stainless steel	277 x 54 x 72 mm	4106030929291

TS 3000 EN 3

COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, rectangular shape

Designation	Description	Ident-No.	Colour	Dimensions	EAN
Cover cap door closer *	for TS 3000 / TS 2000, square, can only be used for door leaf installation	092924	Satin stainless steel	237 x 54 x 72 mm	4106030929246
Cover cap door closer *	for TS 3000 / TS 2000, square, can only be used for door leaf installation	092923	Polished stainless steel	237 x 54 x 72 mm	4106030929239

INSTALLATION MATERIAL

MOUNTING PLATE DOOR CLOSER

for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1

Designation	Description	Ident-No.	Colour	Dimensions	Material
Mounting plate door closer *	for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1	011232	dark bronze	226 x 60 x 5 mm	Aluminum
Mounting plate door closer	for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1	011233	white RAL 9016	226 x 60 x 5 mm	Aluminum
Mounting plate door closer *	for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1	135237	black RAL 9005	226 x 60 x 5 mm	Aluminum
Mounting plate door closer	for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1	011230	silver-coloured	226 x 60 x 5 mm	Aluminum
Mounting plate door closer	for TS 3000 with hole pattern according to DIN EN 1154 Supplement 1	011234	according to RAL	226 x 60 x 5 mm	Aluminum

MOUNTING PLATE GUIDE RAIL

For standard, ECline, T-Stop and EFS guide rail

TS 3000 EN 3

Designation	Description	Ident-No.	Colour	Material	EAN
Mounting plate guide rail	for standard / ECline / T-Stop / EFS guide rail	001512	silver-coloured	Aluminum	4106030015123
Mounting plate guide rail *	for standard / ECline / T-Stop / EFS guide rail	104515	according to RAL	Aluminum	4042938045155
Mounting plate guide rail	for standard / ECline / T-Stop / EFS guide rail	129252	white RAL 9016	Aluminum	4042938292528

MOUNTING PLATE GUIDE RAIL BG

For standard, ECline, T-Stop and EFS guide rail, opposite hinge side

Designation	Description	Ident-No.	Colour	Material	EAN
Mounting plate guide rail BG	for standard / ECline / T-Stop / EFS guide rail	124684	according to RAL	Aluminum	4042938246842
Mounting plate guide rail BG	for standard / ECline / T-Stop / EFS guide rail	124683	silver-coloured	Aluminum	4042938246835

LINTEL CASING BRACKET

For ECline and T-Stop guide rail

Designation	Description	Ident-No.	Colour	EAN
Lintel casing bracket	For ECline and T-Stop guide rail	115006	silver-coloured	4042938150064
Lintel casing bracket	For ECline and T-Stop guide rail	115007	according to RAL	4042938150071

TS 3000 EN 3

LINTEL CASING BRACKET

For standard guide rail

Designation	Description	Ident-No.	Colour	EAN
Lintel casing bracket *	For standard guide rail	030033	dark bronze	4106030300335
Lintel casing bracket *	For standard guide rail	028393	Stainless steel optic	4106030283935
Lintel casing bracket	For standard guide rail	025657	silver-coloured	4106030256571
Lintel casing bracket	For standard guide rail	025658	according to RAL	4106030256588
Lintel casing bracket	For standard guide rail	030034	white RAL 9016	4106030300342

GLASS CLAMPING SHOE

For TS 3000 / 2000 NV

Designation	Description	Ident-No.	Colour	Pane thickness	Material
Glass clamping shoe	for TS 3000/TS 2000 NV	014835	silver-coloured	10 mm	Aluminum
Glass clamping shoe	for TS 3000/TS 2000 NV	014843	white RAL 9016	10 mm	Aluminum
Glass clamping shoe *	for TS 3000/TS 2000 NV	014836	dark bronze	10 mm	Aluminum
Glass clamping shoe	for TS 3000/TS 2000 NV	014845	according to RAL	10 mm	Aluminum

MOUNTING PLATE AND COUNTERPLATE ALL-GLASS DOOR

For TS 3000 / 2000 NV

Designation	Description	Ident-No.	Colour	Pane thickness	Material
Mounting plate and counterplate all-glass door	for TS 3000/TS 2000 NV	090259	silver-coloured	10 mm	Aluminum

TS 3000 EN 3

DRILLING TEMPLATE DOOR CLOSER

for TS 5000/TS 4000/TS 3000/TS 2000

Designation	Description	Ident-No.	Material	EAN
Drilling template door closer	for TS 5000/TS 4000/TS 3000/TS 2000	053134	Plastic	4106030531340

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.