Product data sheet

Pull handle D-shape *



Stainless steel pull handle pair

AREAS OF APPLICATION

- For timber, plastic, glass and metal leaves
- For glass thicknesses 10 and 12 mm
- For door leaf thicknesses up to 50 mm

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-10-31T07:30:11Z

Pull handle D-shape *

PRODUCT FEATURES

- D-shape - straight
- Stainless steel pipe material
- Two fastening points
- Handle diameter depending on variant
- Total length depending on variant

TECHNICAL DATA

Productname	Pull handle D-shape *
Glass thickness (min.)	10 mm
Glass thickness (max.)	12 mm
Surface	matt
Type of installation	Door leaf installation, Glass installation
Material	Stainless steel

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Pane thickness	Type of installation
Pull handle D-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 22 mm; hole spacing: 300 mm	169819	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation
Pull handle D-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 19 mm; hole spacing: 200 mm	169818	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation
Pull handle D-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 19 mm; hole spacing: 150 mm	169817	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation
Pull handle D-shape *	Push handle set for door thicknesses up to 50 mm and 10-12 mm pane thickness (set) - diameter: 25 mm; hole spacing: 300 mm	169820	Satin stainless steel	10 - 12 mm	Door leaf installation, Glass installation

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.